

KS-6600 / 7300 Series

6615 / 6617 / 7315 / 7317 **Fan-free**



Wall-Mount



Side mount security attachment integrates default audio port, optional MSR and optical finger print sensor



Mic In and Line out and 36 key plus lock keypad and/or MSR and/or Smart card reader

Features

- Fan-free structure with vertical fin Aluminum main unit.
- Easy maintenance, spill proof and multipurpose construction.
- Push-open cover to protect power switch from accidental shutdown of the system, providing extra security to the operation.
- A patented finger release lever "Gear Lock" mechanism easily adjusts the LCD tilt angle from 15° to 70°.
- High quality 15" TFT active matrix LCD panel with 1024x768 resolution (XGA) for KS-6615 / KS-7315 ; 17" TFT active matrix LCD panel with 1280x1024 resolution (SXGA) for KS-6617 / KS-7317.
- Durable resistive type or IR type touch sensor for broad range of application.
- Built-in UPS function to support the system from intermittent power failure (battery is option).
- LCD panel brightness control by hardware buttons or software.



Real mount customer pole display



Customer Display Module
Optional 12.1" / 15" LCD display unit
mounts on rear bracket of ks stand

| Specification | KS-6615Z | KS-6615i | KS-6617Z | KS-6617Z-i | KS-7315Z | KS-7315i | KS-7317Z | KS-7317Z-i |
|---|---|----------|--|------------|---|----------|--|------------|
| Processor | Intel Celeron M 1.5 GHz (1 MB L2 cache, PGA) or Celeron M 1.0 GHz (0 KB L2 cache, option for KS-6615 only) | | | | Intel Celeron M 1.86 GHz (1 MB L2 cache) / Core Duo 1.66GHz or 2.0 GHz (2 MB L2 cache) / Core 2 Duo 2.16 GHz (4 MB L2 cache), all in micro-FCPGA socket | | | |
| System Memory | DDR2 400 MHz SODIMM x 1, max. 1 GB | | | | DDR2 667 MHz SODIMM x 1, max. 2 GB | | | |
| Default Memory | 512 MB | | | | 1 GB | | | |
| Video Memory | Dynamic video memory up to 128 MB | | | | Dynamic video memory up to 224 MB | | | |
| Power Supply | +12V DC power adaptor, 80W | | | | | | | |
| Housing | Aluminum Alloy | | | | | | | |
| Front bezel | Textured | Shiny | Textured | | Textured | Shiny | Textured | |
| Base Stand | Gen 5 slim base (Gen 6 option) , wall-mount | | | | | | | |
| Speakers | Built-in | | | | | | | |
| OS support | Windows XP Pro / WEPOS / POSReady / Windows Vista / Win 7 / Linux | | | | Windows XP Pro / WEPOS / POSReady / Vista (Vista 64 bit for Core 2 Duo CPU models only) / Win 7 | | | |
| Compliance | FCC-A, CE-A, RoHs, WEEE | | | | | | | |
| Display | | | | | | | | |
| LCD | 15" LCD, 1024x768 (XGA) | | 17" LCD, 1280x1024 (SXGA) | | 15" LCD, 1024x768 (XGA) | | 17" LCD, 1280x1024 (SXGA) | |
| Touch Sensor | Resistive | Infrared | Resistive | Infrared | Resistive | Infrared | Resistive | Infrared |
| Touch Controller | USB for resistive touch or RS232 interface for IR touch | | | | | | | |
| Brightness Control | Either by hardware push button switch control or by software control | | | | | | | |
| Tilt Adjustment | From 15° to 70° | | | | | | | |
| Expansion | | | | | | | | |
| Storage Device | 2.5" 80 GB SATA HDD or CF memory card (option) | | | | | | | |
| Connectivity | | | | | | | | |
| Audio Port | Built-in:2 internal 2W speakers with stereo audio amplifier and Mic. in / line out ports | | | | | | | |
| CF card slot (Type II , memory card only) | Optional | | | | | | | |
| LAN Port | 10 / 100 / 1000 Mb | | | | | | | |
| Parallel Port | x 1 | | | | | | | |
| Serial Port | DB9 x 4, with + 5 V power supply capability | | | | | | | |
| UPS Port | Yes | | | | | | | |
| Standard USB Port | 6 USB 2.0, 4 in I/O plate, 2 in side cover | | | | | | | |
| Proprietary USB Port | 1 for side mount option | | | | | | | |
| VGA Port | D-Sub 15 pin | | | | | | | |
| CR Port | x 1 | | | | | | | |
| Physical Dimension | | | | | | | | |
| Dimension (W x D x H in mm) | LCD@15° tilt angle: 378 x 321 x 362 LCD@70° tilt angle: 378 x 304 x 294 | | LCD@15° tilt angle: 426 x 326 x 418 LCD@70° tilt angle: 426 x 354 x 319 | | LCD@15° tilt angle: 378 x 321 x 362 LCD@70° tilt angle: 378 x 304 x 294 | | LCD@15° tilt angle: 426 x 326 x 418 LCD@70° tilt angle: 426 x 354 x 319 | |
| Weight (N. W. in kg) | 9.7 | | 12.5 | | 9.7 | | 12.5 | |
| Environment | | | | | | | | |
| Operation Condition | 5°C~+40°C (41°F~+104°F), 20%RH~80%RH, non-condensing max. wet bulb 26°C (78.8°F) | | | | | | | |
| Storage Condition | -20°C~60°C (-4°F~140°F) without UPS battery, -20°C~50°C (-4°F~122°F) with UPS battery, 10%RH~80%RH, non-condensing max. wet bulb 28.9°C (84.0°F) | | | | | | | |
| Options | | | | | | | | |
| 2 nd HDD | YES | | | | | | | |
| 2 nd LCD display | 12" LM-6101; 15" LM-6501, VGA port | | | | | | | |
| Customer Pole Display | PD-2602: Base mount 9 mm VFD pole display, 5 x 7 matrix, RS232 or USB interface PD-306: Base mount 9 mm LCD pole display, 5 x 7 matrix, RS232 or USB interface | | | | | | | |
| SD-400T SD-800 | SD-400T: MSR and/or Finger print sensor SD-800: MSR and/or Wifi Module and/or RFID Module | | | | | | | |
| KP-300W-R | Mic In and Line out and 36 key plus lock keypad and/or MSR and/or Smart card reader | | | | | | | |
| UPS Battery | 2.3 AHr / 12 V in base | | | | | | | |

❖ The product information and specifications are subject to change without prior notice.

2010 V.02

Posiflex Technology, Inc.

6, Wu-Chuan Road, Wu Ku, Taipei, Taiwan
Tel: 886 2 2299-1599 Fax: 886 2 2299-1819
sales@posiflex.com.tw www.posiflex.com

